

COLORado™ 1-Quad Zoom Tour



The COLORado™ 1-Quad Zoom Tour is a compact, tour-ready wash light featuring seven bright quad-color (RGBW) LEDs, giving the user a bright beam with zoom for versatile usage in the studio, on set, or on the road. The incorporation of a wide range zoom and five dimming curves lends immense flexibility to designers who can use the same fixtures to highlight specific areas and flood a stage. Secure Neutrik® powerCON® and direct 3- and 5-pin DMX connectors ease installation. COLORado™ 1-Quad Zoom Tour also includes an attachable gel frame holder.

FEATURES

- Built-in auto and custom programs recalled via DMX and Master/Slave
- RGBW color mixing via DMX or manually
- Zoomable, with a wide zoom range for design versatility
- Tough road-ready construction
- Individual control of outer pixel ring and center pixel
- Selectable, smooth dimming curves for programming versatility
- 16-bit dimming of individual colors as well as master dimmer
- Neutrik® powerCON® power input/output connections
- 3- and 5-pin DMX input/output connections

SPECIFICATIONS

- DMX Channels: 3, 4, 5, 6, 7, 10, 12, 17 or 25
- Data Connectors: 3- and 5-pin XLR
- Light Source: 7 LEDs (quad-color RGBW) 15 W, (1,000 mA), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes
- Accessory Holder/
Gel Frame Size: 7.5 in (191 mm)
- Dimmer: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 7° to 29°
- Field Angle: 16° to 48°
- Zoom Angle: 16° to 48°
- Dimming Modes: 9
- Illuminance (16°): 3,950 lux @ 5 m
- Illuminance (48°): 330 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 12 units @ 120 V; 21 units @ 208 V; 23 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 129 W, 1.08 A @ 120 V, 60 Hz
- Power and Current: 125 W, 0.63 A @ 208 V, 60 Hz
- Power and Current: 124 W, 0.57 A @ 230 V, 50 Hz
- Weight: 14.8 lb (6.7 kg)
- Dimensions: 13.14 x 9.25 x 7.48 in (334 x 235 x 190 mm)
- Approvals: CE, MET