

SOLARIS LED™

Introducing the
Incredible

FLARE JR!

Full
RDM
Functionality

Available with
(((↑)))
Wireless Option



Little brother of the fabulous
Solaris LED Flare, winner
Live Design 2013 Product
of the Year and PLASA 2013
Sustainability Award



Super Bright LED RGBW Wash/Strobe/Blinder

MORE SAVINGS! Simultaneous color wash and strobe in ONE fixture – Saves labor, time, space, energy, and cost.

MORE SMOOTH! Instantaneous RGBW color mixing with 1200Hz refresh rate – Smooth on-camera dimming.

MORE VERSATILE! Pixel-map feature divides into 1, 2, or 4 sections for ultimate control.

MORE SATURATED COLORS! Intense, deep reds and blues. Ultra-bright greens. Brilliant camera-friendly whites.

MORE FLEXIBLE! 36-degree beam angle optimized for most applications.



Production Supplies & Services Worldwide

tmb-info@tmb.com

LOS ANGELES

LONDON

NEW YORK

BEIJING

TORONTO

Tel: +1 818.899.8818

Tel: +44 (0)20.8574.9700

Tel: +1 201.896.8600

Tel: +86 10.8492.1587

Tel: +1 519.538.0888

© TMB

FLARE[™]JR

SPECIFICATIONS

Light sources	32 10W CREE [®] LEDs (divided in to 4 pixels)
Beam Spread	36°
Colors	4- R, G, B, W
Average color wavelength (manufacturer rated)	red: 625 nm
	green: 530 nm
	blue: 460 nm
	white: >5700K
Refresh rate	1200 Hz
Intensity control	16bit or 8bit
Control	DMX-512
AC Power	100-240VAC Universal Input, 50/60 Hz, ~400 W
Cooling	air-cooled fan
Operating Temperature	-20°C - +40°C
DMX Channels	3-24 depending on control mode
DMX Connectors	In/Out - XLR 5-pin F/M
Max. power draw	~400 W
Power Connectors	In- PowerCON 20A blue + THRU- PowerCON Grey
Fixing	Adjustable yoke
Fixture body	Powdercoated steel
Unit Dimensions (HxWxD)	6.1 x 13.4 x 5.3 in (15.5 x 34 x 13.5 cm)
Shipping Dimensions (HxWxD)	TBA
Unit Weight	10.6 lb (4.8 kg)
Shipping weight	12 lb (5.4 kg)

Specifications and features are subject to change without notice.

