



Mole-Richardson Co.

TYPE 2941

**2,000 WATT
MOLEQUARTZ®
2K NOOKLITE**



FEATURES

This versatile lighting fixture is a very portable and compact source of illumination. Its reflector provides a wide, even field of light which makes it ideal for general "fill," background light, or "bounce" light. Equipped with safety screen.



TYPE 2941 MOLEQUARTZ® NOOKLITE
MOUNTED ON TYPE 2541 COMPACT
LITEWATE BABY SIZE STAND



Mole-Richardson Co.

TYPE 2941 
2,000 WATT
MOLEQUARTZ®
2K NOOKLITE



SPECIFICATIONS

HEAD: Type 2941, 2,000 watts.
RATING: 120/240 volts, A.C. or D.C., 16.7 amps max.—2,000 watts max.
SOCKETS: Compressible single contract. (Two per globe).
CABLE: Attached 25 ft., Type SO, 3 conductor #14 AWG. (Specify type of plug when ordering).
SWITCH: Thru-cord type in cable.
CONSTRUCTION: Solid and perforated sheet steel.
YOKE: Cast aluminum. Fits any standard 5/8" dia. stand spud or 5/8" hanger spud.
REFLECTOR: Aluminum, special Molebrite® Alzak surface.
SIZE: 12" x 5 3/8" x 2 1/2".
FINISH: Maroon Powder Coat Enamel
HEAD WEIGHT: 8 1/4 lbs. (w/cable).

ACCESSORIES

- 2942 2-Leaf Light Shield
- 2944 4-Leaf Light Shield
- 2945 Accessory Holder
- 2948S Single Moledura Scrim (8 5/8" x 9 15/16")
Accessory Holder needed for mounting.
- 2948D Double Moledura Scrim (8 5/8" x 9 15/16")
Accessory Holder needed for mounting.
- 2946 Blue Molocolor Daylight Conversion Filter
Accessory Holder needed for mounting.
- 2947 Dichroic Daylight Conversion Filter
Accessory Holder needed for mounting.
- G137 Scrim Bag
- 500848 C-Clamp and Adapter
- 2541 Compact Litewate Baby Size Stand
(See Stand Section for more information & options)

GLOBE TABLE

Base, recessed single contact. Burn any position. T-6 bulb or T-8 bulb; 5 5/8" M.O.L.

| Watts | Ordering Code | Color Temp.*K | Finish | Volts | Life Hours | Amps |
|-------|---------------|---------------|--------|-------|------------|------|
| 2000 | FEY | 3200 | Clear | 120 | 500 | 16.7 |
| 2000 | FEX | 3200 | Clear | 240 | 300 | 8.3 |
| 1000 | FER | 3200 | Clear | 120 | 500 | 8.3 |
| 1000 | DWT | 3000 | Clear | 120 | 2000 | 8.3 |

Globes not included in price of lamp.
 See price list for complete details.




Type 2944
4-Way Light Shield



Type 2945
Accessory Holder



Type 2948S
Single Moledura Scrim



Type 2947 Dichroic
Daylight Conversion Filter



Type G137
Scrim Bag

PERFORMANCE DATA

Using FEY-Q20008/4CL, 2,000 Watt, 120 volt, 3200° K quartz globe.

| Distance Feet | Light Intensity F.C. | Lighted Area Dimension*—Feet | |
|---------------|----------------------|------------------------------|--------|
| | | Width | Height |
| 5 | 1,000 | 8.5 | 4.4 |
| 10 | 250 | 17.1 | 8.7 |
| 15 | 110 | 25.6 | 13.1 |
| 20 | 60 | 34.2 | 17.5 |
| 25 | 40 | 42.7 | 21.9 |
| 30 | 27 | 51.2 | 26.2 |

*Light tapers smoothly at edge of field. Dimensions listed define flat area boundaries at which the intensities are approximately 50% of tabulated intensities at beam center.

