



KINO FLO[®]
Lighting Systems

SELECT

LED



Select LED DMX



The Select LED's have the versatility and unique features which make it the perfect imaging tool for use in any studio production or on location. The detachable controller can operate the fixtures remotely with a 25ft (8m) extension cable. For further flexibility, the controller can be attached to the back of the fixture or mounted onto a stand using the ballast mount (MTP-BAL) accessory. Slim in profile at only 3.5 inches, the portable, lightweight fixture can be rigged in tight places or screwed onto a wall or ceiling through its eyelets.

The Select LED lights include dial-in variable color temperature control, full-range dimming and programmable 2700K to 6500K presets. The Select LED's soft white light is flicker-free and does not shift color temperature when dimmed. Light levels are consistent throughout the Kelvin range.

In addition, Kino Flo introduces a Green/Magenta control to match the spectral sensitive curves of the most popular cameras and other light sources. With built-in DMX and Lumen Radio® receivers, the Select LED's can be controlled by DMX and/or DMX wireless. Wireless capability eliminates the need for DMX cables. Rounding out the Select LED's attributes is the ability to run on universal input from 100-240VAC, or 24VDC with as little as 1.3A, 120VAC.

Features include:

- Kelvin presets & custom settings, 2700K-6500K
- Universal input 100-240VAC or 24VDC
- Remote controller
- Manual and DMX dimming w/ Auto Terminate
- DMX wireless (Lumen Radio)
- Green/Magenta control
- Flicker-free, dead quiet operation
- Built-in Barndoors
- Twist-on locking Center Mount

▼ Select LED DMX Systems



CFX-SL30
Select LED 30 Fixture



CFX-SL20
Select LED 20 Fixture



LED-150X-120U
Select LED 150 DMX Controller, Univ 120U



LED-150X-230U
Select LED 150 DMX Controller, Univ 230U



MTP-BC41
Kino 41K Mount w/
Baby Receiver Curve (16mm)



X12-25
Select LED 150 Extension, 25ft

▼ Photometrics

Select 30	FC	510	161	75	43	28	20	15	11	9	8
	Feet	2	4	6	8	10	12	14	16	18	20
Select 20	FC	508	154	70	40	26	18	14	11	9	7
	Feet	2	4	6	8	10	12	14	16	18	20

Select 30	LUX	7270	2470	1190	683	445	312	233	181	146	117
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5
Select 20	LUX	7113	2409	1121	634	412	288	212	164	131	106
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ LED Fixture Specifications

Fixture	Kelvin Range	Dimming Range	Dimensions	Weight
Select 30	2700-6500	100%-1%	40.5 x 10.5 x 3.5" w/ 6.5" barndoors (103 x 27 x 9cm w/ 16.5cm barndoors)	12 lb (5kg)
Select 20	2700-6500	100%-1%	26.5 x 13 x 3.5" w/ 6" barndoors (67 x 33 x 9cm w/ 15cm barndoors)	10 lb (4.5kg)

▼ LED Controller Specifications

Controller	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps 24VDC	Kelvin Range	Dimming Range	Dimensions	Weight
LED-150X	100-240VAC, 50/60Hz, 150W	1.3A	18-36VDC, 150W	7.0A	2700-6500	100%-1%	15 x 4.5 x 3" (38 x 11.5 x 8cm)	4.5 lb (2kg)
LED-150X	240-100VAC, 50/60Hz, 150W	0.65A	18-36VDC, 150W	7.0A	2700-6500	100%-1%	15 x 4.5 x 3" (38 x 11.5 x 8cm)	4.5 lb (2kg)

▼ Details



▼ Select LED DMX Systems



SYS-S30-120U

Select LED 30 DMX System, Univ 120U

Contents

- 1 Select LED 30 Fixture
- 1 Select LED 150 DMX Controller
- 1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)
- 1 Extension, 25ft

SYS-S30-230U

Select LED 30 DMX System, Univ 230U



SYS-S20-120U

Select LED 20 DMX System, Univ 120U

Contents

- 1 Select LED 20 Fixture
- 1 Select LED 150 DMX Controller
- 1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)
- 1 Extension, 25ft

SYS-S20-230U

Select LED 20 DMX System, Univ 230U

▼ Select LED DMX Accessories/ Cases



DFS-SL30-H
Select 30 Flozier, Half




MTP-KF41
Kino 41K Mount
w/ 3/8" Pin (10mm)



MTP-BAL
Kino Ballast Baby Mount
(16mm)



BAG-SL30
Select LED 30 Soft Case



LVR-SL390-P
Select 30 Louver/HP, 90°




MTP-BF41S
Kino 41K Mount
w/ Baby Receiver Short
(16mm)



STD-M36
Medium Duty, 36"



KAS-DL30
Select LED 30 Flight Case



LVR-SL360-P
Select 30 Louver/HP, 60°



MTP-B41F
Kino Offset w/
Baby Receiver (16mm)



STD-M30
Medium Duty, 30"



KAS-DL20
Select LED 20 Flight Case



LVR-SL290-P
Select 20 Louver/HP, 90°



STD-D1
Reverse Stand



KAS-SL32
Gaffer LED 30 Ship Case (2-Unit)



LVR-SL260-P
Select 20 Louver/HP, 60°



KAS-SL22
Interview LED 20 Ship Case (2-Unit)

KAS-SL33
Select LED 30 Ship Case (3-Unit)

KAS-SL23
Select LED 20 Ship Case (3-Unit)

Select LED DMX Kits

▼ Select LED 30 DMX Kits



KIT-S30B-120U
Select LED 30 DMX Kit, Univ 120U w/ Soft Case

KIT-S30B-230U
Select LED 30 DMX Kit, Univ 230U w/ Soft Case

Contents	Dimensions	Weight
1 Select LED 30 Fixture	42.5 x 7.5 x 16.5"	26 lb (12kg)
1 Select LED 150 DMX Controller	(108 x 19 x 42cm)	
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Soft Case		



KIT-S30-120U
Select LED 30 DMX Kit, Univ 120U w/ Flight Case

KIT-S30-230U
Select LED 30 DMX Kit, Univ 230U w/ Flight Case

Contents	Dimensions	Weight
1 Select LED 30 Fixture	46 x 11 x 16.5"	46.5 lb (21kg)
1 Select LED 150 DMX Controller	(117 x 28 x 42cm)	
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Flight Case		



KIT-S32-120U
Gaffer LED 30 DMX Kit, Univ 120U (2-Unit)

KIT-S32-230U
Gaffer LED 30 DMX Kit, Univ 230U (2-Unit)

Contents	Dimensions	Weight
2 Select LED 30 Fixture	43.5 x 13 x 18.5"	69 lb (31kg)
2 Select LED 150 DMX Controller	(110.5 x 33 x 47cm)	
2 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
2 Extension, 25ft		
1 Ship Case		

▼ Select LED 20 DMX Kits



KIT-S20B-120U
Select LED 20 DMX Kit, Univ 120U w/ Soft Case

KIT-S20B-230U
Select LED 20 DMX Kit, Univ 230U w/ Soft Case

Contents	Dimensions	Weight
1 Select LED 20 Fixture	31 x 7.5 x 18"	23 lb (10.5kg)
1 Select LED 150 DMX Controller	(79 x 19 x 46cm)	
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Soft Case		



KIT-S20-120U
Select LED 20 DMX Kit, Univ 120U w/ Flight Case

KIT-S20-230U
Select LED 20 DMX Kit, Univ 230U w/ Flight Case

Contents	Dimensions	Weight
1 Select LED 20 Fixture	30 x 10.5 x 21"	38 lb (17kg)
1 Select LED 150 DMX Controller	(76 x 27 x 53cm)	
1 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
1 Extension, 25ft		
1 Flight Case		



KIT-S22-120U
Interview LED 20 DMX Kit, Univ 120U (2-Unit)

KIT-S22-230U
Interview LED 20 DMX Kit, Univ 230U (2-Unit)

Contents	Dimensions	Weight
2 Select LED 20 Fixture	36 x 13 x 20.5"	63.5 lb (29kg)
2 Select LED 150 DMX Controller	(91.5 x 33 x 52cm)	
2 MTP-BC41 Mount w/ Baby Receiver Curve (16mm)		
2 Extension, 25ft		
1 Ship Case		



Kino Flo Lighting Systems
2840 North Hollywood Way
Burbank, CA 91505

+1 818 767 6528 voice +1 818 767 7517 fax

www.kinoflo.com

© Kino Flo Select LED
No. 3110095 Rev B