



KINO FLO[®]
Lighting Systems

celeb[®] 401Q



Simply **Brilliant** LED

Celeb[®] 401Q DMX LED



▼ Photometrics

	FC	1090	331	152	87	57	40	30	23	19	15
	Feet	2	4	6	8	10	12	14	16	18	20
Celeb 401Q	LUX	15800	5120	2360	1370	892	628	467	363	292	237
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps 24VDC	Kelvin Range	Dimming Range	Dimensions	Weight
Celeb 401Q DMX Yoke	100-240VAC, 50/60Hz, 210W	1.8A	18-28VDC, 198W	8.25A	2700-6500	100%-1%	30 x 26 x 5" (76 x 66 x 13cm)	24 lb (11kg)
Celeb 401Q DMX Yoke	240-100VAC, 50/60Hz, 207W	1.0A	18-28VDC, 198W	8.25A	2700-6500	100%-1%	30 x 26 x 5" (76 x 66 x 13cm)	24 lb (11kg)

▼ Details



The Celeb[®] 401Q DMX LED features new technical innovations that make it an ideal professional imaging tool: dial-in white light from 2700K to 6500K, presets and programmable settings, full-range dimming and DMX wireless link capability. With soft, even True Match[®] light quality (CRI 95), the Celeb 401Q runs on universal input from 100VAC-240VAC or 24VDC. The slim, square fixture emits more lumens than a 1K softlight, yet uses only 1.8A (120VAC). The soft, beauty light doesn't flicker or shift color when dimmed. Light levels do not change when selecting Kelvin settings. With a Lumen Radio transmitter, the Celeb 401Q can operate on DMX wireless. Features include:

- Kelvin presets & custom settings between 2700K-6500K
- Universal Input 100-240VAC or 24VDC
- Onboard and DMX dimming w/ Auto Terminate
- DMX wireless link (Lumen Radio)
- Flicker-free, dead quiet operation
- Gel Frame and Honeycomb Louver
- Yoke Mount and Pole-Op

▼ Celeb 401Q DMX LED Kit



KIT-C401Q-120U
Celeb 401Q DMX Yoke Mount Kit, Univ 120U

KIT-C401Q-230U
Celeb 401Q DMX Yoke Mount Kit, Univ 230U

Contents
1 Celeb 401Q DMX Yoke
1 Jr. Pin
1 Ship Case

Dimensions
34.5 x 33 x 8.5"
(88 x 84 x 22cm)

Weight
52 lb
(24kg)


▼ Celeb 401Q DMX LED Yoke



CEL-401Q-120U
Celeb 401Q DMX Yoke Mount, Univ 120U



CEL-401Q-230U
Celeb 401Q DMX Yoke Mount, Univ 230U



GFR-CE4-Q
Celeb 401Q Gel Frame (Included)

LVR-CE490-Q
Celeb 401Q Louver, 90° (Included)


▼ Celeb 401Q DMX LED Pole-Op



CEL-401QP-120U
Celeb 401Q DMX Pole-Op, Univ 120U



CEL-401QP-230U
Celeb 401Q DMX Pole-Op, Univ 230U




GFR-CE4-Q
Celeb 401Q Gel Frame (Included)

LVR-CE490-Q
Celeb 401Q Louver, 90° (Included)

▼ Celeb 401Q DMX LED Accessories/ Case



BRD-CE4-Q
Celeb 401Q Barndoors (Set of 4)



LVR-CE460-Q
Celeb 401Q Louver, 60°



MTP-180
Junior Pin Assembly for Yoke (28mm)



7010048
Celeb 401Q Yoke Assembly



7010049
Celeb 401Q Pole-Op Assembly



KAS-CE4-Q
Celeb 401Q Yoke Ship Case



KINO FLO[®]
Lighting Systems

2840 North Hollywood Way, Burbank CA 91505

+1 818 767 6528 voice

www.kinoflo.com

No. 3110091 Rev B