



impression 
X4

THE IMPRESSION X4 IN BRIEF

LIGHT SOURCE

19 High Power RGBW LEDs

OPTICAL SYSTEM

Motorized zoom system with
7° to 50° beam angle
15W Quad color LED's

MOVEMENT

8 or 16 bit resolution
Position feedback
Maximum speed:
660° pan in 2 sec
260° tilt in 1 sec
High precision 3 phase
stepping motor control

SHUTTER / DIMMER

Continuous dimmer 0-100%
Variable speed strobe of 1-10 Hz.
Random strobe effect
Pulse effects

CONTROL

DMX-512 protocol
Macro operation of individual lenses
Convection cooling
Optional very quiet
temperature controlled ventilation
Internal color presets, and
variable color temperature control
Backlit graphic LCD menu
with 4 illuminated buttons
Over-temperature protection
Color calibration feature

POWER SUPPLY

Power consumption: 350VA (Watt)
Power input: Auto sensing
100-240 VAC / 50-60Hz
Fuse protection:
Microfuse 20mm, T 5A

CONNECTORS

DMX: XLR 5 pin
Mains voltage: Neutrik Powercon

OPERATING CONDITIONS

Maximum ambient
temperature: 113°F / 45°C

MOUNTING OPTIONS

Upright: Floor stand (supplied)
with brackets for ratchet strap
Built-in M10 socket for
half-coupler or other clamp
2 attachment points for safety wires
Optional omega bracket attachment
Optional adjustable bar for
vertical truss mounting

SHIPPING

cardboard box
4 way tourpack (complete with
half couplers) in flight case
6 way tourpack (complete with
half couplers) in flight case

HOUSING COLORS

Standard colors are
black, silver & white
For other colors please
contact sales department

DIMENSIONS

Length x width x height
(head vertical):
6.5 x 13 x 15 inches /
165mm x 330mm x 381mm

NET WEIGHT

16 lbs / 7.3 kg



It's time to feast your eyes on
something new...

impression[®]
X4



GLP German Light Products, Inc.
10945 Pendleton Street
Sun Valley, CA 91352
Tel: +1.818.767.8899 Fax: 1.818.279.9898
www.germanlightproducts.com info@germanlightproducts.com

