

EPAR TRI



MAIN FEATURES

- . 14 x 3W TRI RGB LEDs
- . Dual Yoke Floor Stand
- . Superior Color Mixing
- . Compact Housing
- . No Colored Shadows
- . Flicker Free Operation

PRODUCT FEATURES

- . 14 x 3W TRI RGB LEDs
- . No Colored Shadows and perfect Tri color mixing
- . Long Life LEDs (rated at 50.000 Hours)
- . 10° standard beam angle
- . Aluminum body
- . Flicker free operation for television and film
- . USITT DMX 512
- . 1/2/3/4/6/7 DMX Channel operation mode
- . Auto Programs and Manual Control
- . Holds last state when power off
- . 0-100% Dimming
- . Variable Strobe effect
- . 3 pin XLR in/out
- . Integrated Floor Stand / Dual Yoke bracket
- . Gel Frame included
- . Electronic Switching Power Supply
- . Power Consumption: 70W Max
- . 100-240V AC, 50/60Hz (Multi-voltage)
- . Dimensions: 10"x8.5"x11" / 252x216x281mm
- . Weight: 9 lbs. / 4.1 Kg

www.elationlighting.com

Toll Free (866) 245-6726

Specifications are preliminary & are subject to change without notice
©Elation Professional • Los Angeles, Ca USA • Kerkeade, Netherlands

EPAR TRI

Photometric Beam Angle Data

Standard 10° Beam Angle

LUX x 0.0929 = FC

| | | | |
|------------|---------------------|-------------------|-------------------|
| R | 319 FC / 3433 LUX | 78 FC / 842 LUX | 36 FC / 392 LUX |
| G | 1196 FC / 12870 LUX | 311 FC / 3347 LUX | 141 FC / 1515 LUX |
| B | 134 FC / 1440 LUX | 40 FC / 420 LUX | 19 FC / 200 LUX |
| ALL | 1512 FC / 16280 LUX | 393 FC / 4230 LUX | 180 FC / 1933 LUX |

