

# PresentationPRO-II

PresentationPRO-II simplifies presentations, live events, corporate boardrooms, and church services.



**PRODUCT SPECIFICATIONS****PRESENTATIONPRO-II****Scaled Video Channel Inputs****Input Types**

- Analog Inputs (8) - RGBHV/RGBS/RGsB computer video, YPbPr video (SD or HD), S-video, or Composite video on 15-pin HD connector
- SDI Input (1) – per SMPTE 259M-C on BNC connector (PresentationPRO-II Digital Only)

**Input Resolutions**

- PAL or NTSC
- Computer Resolutions VGA (640 x 480) through UXGA (1600 x 1200)
- HDTV Resolutions up to 1920 x 1080 (720p, 1080i, 1080p)
- Plasma Display Resolutions

**Unscaled Background Key Channel Input Optional****Input Types**

DVI Digital Input - per DDWG 1.0 on DVI-I connector

**Input Resolutions**

Resolution must be same as selected output resolution.

**Outputs****Output Types**

- Analog Output - RGBHV/RGBS/RGsB (non-interlaced only) on 15-pin HD connectors
- DVI Digital Output - per DDWG 1.0 on DVI-I connector

**Output Resolutions**

- Computer Resolutions VGA (640 x 480) through UXGA (1600 x 1200)
- HDTV Resolutions, progressive up to 1920 x 1080(1080p)
- Plasma Display Resolutions

**User Control****Front Panel Control**

LCD TouchScreen Display, Keyboard circuitry, Rotary Encoders and LED lighted push buttons

**Remote Control**

The unit may be controlled from a computer or external controller via LAN or an RS-232 serial link.

Control functions include:

- Source Input Configuration
- Output Format Selection
- Test Pattern Selection
- Video Source Selection
- Transition Effect Selection

Last updated: 21 Jan 2014

Technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest information.