

Pro G7905U WUXGA 3LCD Projector with 4K Enhancement

Projectors

Large Venue



Premium large-venue projector with 4K Enhancement and powered lenses.

3x Higher Color Brightness¹ and reliable performance — 3LCD, 3-chip technology

One measurement of brightness is not enough — look for both high color brightness and high white brightness. The Pro G7905U has:

Color Brightness: 7,000 lumens²

White Brightness: 7,000 lumens²

Exceptional Full HD widescreen display — native WUXGA (1920 x 1200) with 4K Enhancement³ for presentations, videos, digital signage and more

4K Enhancement Technology³ — a revolutionary technology that accepts 4K signal and enhances 1080p for output that surpasses Full HD image quality

Versatile connectivity — supports the full range of inputs, including HDBaseT™, HDMI®, DVI-D, VGA and 5-BNC, for easy integration with any system

Dynamic projection capabilities — advanced built-in Edge Blending, image warping and curved-surface correction technologies for a variety of applications

Nine optional interchangeable lenses — with powered lens shift and lens memory, including an ultra short-throw lens for shallow spaces (one lens included)

Web-based remote management — control and monitor projector status via a Web browser

Professional installation features — full 360-degree installation flexibility, including Portrait Mode



Specifications

Projection System High-aperture Epson[®] 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Pixel Number 2,304,000 dots (1920 x 1200) x 3
Native Resolution 1920 x 1200 (WUXGA)
Resize 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050
Aspect Ratio Supports 4:3, 16:9, 16:10
Pixel Arrangement Cross stripe
Color Brightness² Color Light Output: 7,000 lumens
White Brightness² White Light Output: 7,000 lumens
Contrast Ratio 50,000:1 (Full White 7,000 lm / Full Black 0 lm)
Brightness Uniformity (typical) 90%
Color Reproduction Up to 1 billion colors
Size (projected distance) 50" - 300"
Lens Shift Vertical: ±67 percent; horizontal: ±30 percent
Keystone Correction Vertical: ±45 degrees; horizontal: ±30 degrees
Lamp Type 400 W UHE
Lamp Life* (ECO Mode/Normal) Up to 4,000/3,000 hours

Projection Lens (Standard)

See website for information on optional lenses.
Type Powered focus/zoom
F-number 1.70 - 2.30
Focal Length 24.0 mm - 38.2 mm
Zoom Ratio Optical zoom 1 - 1.6x
Throw Ratio Range 1.44 - 2.32

Other Features

Operating Temperature 32 ° to 113 °F (0 ° to 45 °C)
Power Supply Voltage 100 - 240 V ±10%, 50/60 Hz AC
Power Consumption
 601 W (Normal Mode)
 498 W (ECO Mode)
 3.0 W Standby (Communication on)
 0.5 W Standby (Communication off)
Fan Noise 39 dB (Normal Mode); max. 31 dB (ECO Mode)
Security Security cable hole, lens lock, Kensington lock provision

Effective Scanning Frequency Range

Pixel Clock 13.5 MHz - 162 MHz (up to UXGA 60 Hz)
Horizontal 15 kHz - 92 kHz
Vertical 50 Hz - 85 Hz

Video I/O

Display Performance NTSC: 480 line, PAL: 576 line (depends on observation of the multi-burst pattern)
Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-AL/PAL60/SECAM/480i/576i/480p/576p/720p/1080i/1080p
Pixelworks[®] Video Chip 3D Y/C separation, noise reduction motion compensated Interlace-Progressive conversion (2 - 2, 3 - 2 film detection)

Interfaces

HDBaseT x 1
 DVI-D x1
 HDMI x 1
 Computer: D-sub 15 pin x 1
 Component Video: BNC x 1
 Audio-in: Mini stereo x 3
 Audio Out x 1
 Network: RJ-45 x 1, 100 Mbps Serial: RS-232c
 Hardwire remote jack x 1
 Monitor Out: D-sub 15 pin x 1

Dimensions (W x D x H)

Excluding Feet, Lens 19.88" x 15.04" x 5.67"
Weight 19.6 lb
Including Feet, Lens 19.88" x 15.94" x 6.73"
Weight 28.4 lb

Remote Control

Features Power, source search selection, computer, video, A/V Mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions
Operating Angle
 Right/left: Front: ± 60 degrees; Rear: ± 30 degrees
 Upper/lower: Front: ± 20 degrees; Rear: +10 to +50 degrees
Operating Distance 49 ft

Eco Features

RoHS compliant
 Recyclable product[†]
 Epson America, Inc. is a SmartWay[®] Transport Partner[®]

Support

The Epson ConnectionSM
 Pre-sales support U.S. and Canada 800-463-7766
 Internet website www.epson.com

Service Programs

Limited warranty of 20,000 hours of usage or 3 years, whichever comes first, Epson Road Service program, PrivateLine[®] dedicated toll-free support (U.S. and Canada only) and 90-day limited lamp warranty

What's in the Box

Pro G7905U projector, a lens, power cable, computer cable (VGA), projector remote control with batteries, user manual CD, EasyMP[®] software CD, Quick Setup Sheet and lens lock screw



Ordering Information

Pro G7905U	V11H749120
Genuine Epson lamp (ELPLP93)	V13H010L93
Replacement air filter (ELPAF30)	V13H134A30
Ultra short-throw zoom Lens	V12H004X01
Short-throw #1 zoom Lens	V12H004U03
Short-throw #2 zoom Lens	V12H004U04
Wide-throw #1 zoom Lens	V12H004W05
Wide-throw #2 zoom Lens	V12H004W06
Middle-throw #1 zoom Lens	V12H004M08
Middle-throw #2 zoom Lens	V12H004M09
Middle-throw #3 zoom Lens	V12H004M10
Middle-throw #4 zoom Lens	V12H004M11
Long-throw zoom Lens	V12H004L08
Quick Wireless Connect key (ELPAP10)	V12H731P02
Epson Ceiling Mount - low ceilings (ELPMB47)	V12H802010
Epson Ceiling Mount - high ceilings (ELPMB48)	V12H803010
Advanced projector ceiling mount with precision gear	ELPMBPRH
Adjustable suspended ceiling channel kit	ELPMBP01
False ceiling plate kit	ELPMBP02
Structural round ceiling plate	ELPMBP03
Adjustable extension column (pipe) 8" - 11"	ELPMB001
Kensington security lock	ELPSL01
Distribution amplifier	ELPDA01
HDBaseT Transmitter (ELPHD01)	V12H547020
Wireless LAN module (ELPAP10)	V12H731P02
1-year extended warranty	EPPEXPB1
2-year extended warranty	EPPTPB2

1 Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. The projectors used by a third-party lab for measuring color brightness were leading Epson 3LCD business and education projectors and leading 1-chip DLP projectors, based on NPD sales data for June 2013 through May 2014 and PMA Research sales data for Q1 through Q3 2013. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality. | 4 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | 5 For convenient and reasonable recycling options, visit www.epson.com/recycle | 6 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Contact:



Specifications and terms are subject to change without notice. EPSON and EasyMP are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52342 8/16