

Tile	BP3	BP3 Triangle	BP3 90 Degree Corner	BP3 Round Corner
Pixel Pitch	3.91mm	3.91mm	3.91mm	3.91mm
Max Brightness Calibrated	1500nit	1500nit	1500nit	1500nit
Panel Dimension	500 x 500 x 90 mm 19.69" x 19.69" x 3.54"	500 x 500 x 90 mm 19.69" x 19.69" x 3.54"	500 x 500 x 90 mm 19.69" x 19.69" x 3.54"	500 x 500 x 90 mm 19.69" x 19.69" x 3.54"
Panel Resolution (H x V)	128 x 128	based on 128 x 128	128 x 128	based on 128 x 128
Weight Per Panel	8.7kg; 19.18lbs	6.85kg; 15.10lbs	9.5kg; 20.94lbs	8.7kg; 19.18lbs
Power Consumption Max/Average	160W / 80W	80W / 80W	160W / 80W	120W / 60W
Transparency	Solid	Solid	Solid	Solid
Serviceability	Front / Rear	Front / Rear	Rear	Rear
Processing Platform	Evision	Evision	Evision	Evision
Curving (Concave & Convex)	Concave 10°~Convex 10°	Concave 10°~Convex 10°	Concave 10°~Convex 90°	Concave 10°~Convex 10°
Max. Hanging (panels)	20	20	20	20
Max. Stacking (panels)	8	8	8	8
LED Configuration	SMD 2020 Black	SMD 2020 Black	SMD 2020 Black	SMD 2020 Black
Viewing Angle Vertical	140°	140°	140°	140°
Viewing Angle Horizontal	140°	140°	140°	140°
Multiplexing	16	16	16	16
Refresh Rate	1920	1920	3000	3000
Gray Scale	16bit	16bit	16bit	16bit
Frame Material	Magnesium Alloy	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy
Operational Temp / Humidity	-20°~ 45°C, 10~90% RH -4°~113°F, 10~90% RH	-20°~ 45°C, 10~90% RH -4°~113°F, 10~90% RH	-20°~ 45°C, 10~90% RH -4°~113°F, 10~90% RH	-20°~ 45°C, 10~90% RH -4°~113°F, 10~90% RH
IP Rating (Front / Rear)	Indoor	Indoor	Indoor	Indoor
Certifications	CE, ETL, FCC, ROHS	CE, ETL, FCC, ROHS	CE, ETL, FCC, ROHS	CE, ETL, FCC, ROHS