

# STRIKE 1



## SPECIFICATIONS

### Optical

- Light Source: 1 LED (WW) 230 W, (4.1 A), 2688 K, 50,000 hours life expectancy
- Light Source: 8 LEDs (Amber) 2 W, (0.7 A), 50,000 hours life expectancy
- Color Temperature (at full): 2688 K
- Color Temperature (at 10%): 1941 K
- CRI: 93
- Beam Angle: 30°
- Field Angle: 51°
- Illuminance: 1,119 lux @ 5 m
- Selectable PWM: 600 Hz, 1200 Hz, 2000 Hz, 4000 Hz, 25,000 Hz

### Dynamic Effects

- Dimmer: Electronic
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

### Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Seetronic Powerkon power linking cables
- 5-pin IP or Non-IP DMX Cables
- Strike 1 Multi-Bracket

## FEATURES

- Intense single pod blinder/strobe rated IP65 for all-weather use
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on-the-fly
- Beautiful warm glow made possible with emulated “red shift” to mimic incandescent fixtures
- Multi-bracket allows you to create multi-fixture banks with ease
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM) control to eliminate flicker on camera
- RDM (Remote Device Management) for added flexibility

## Construction / Physical

- Dimensions: 14.96 x 7.40 x 14.61 in (380 x 188 x 371 mm)
- Weight: 18.8 lb (8.6 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast
- Accessory Holder/Gel Frame Size: 8.87 in (225 mm)

## Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

## Control

- Protocol(s): DMX, RDM
- DMX Channels: 1, 3, 4, 5 or 6
- Modes/Personalities: 5 personalities (1ch, 3ch, 4ch, 5ch, 6ch)

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 5 units @ 100 V; 6 units @ 120 V; 10 units @ 208 V; 11 units @ 230 V; 11 units @ 240 V
- Power and Current: 265 W, 2.651 A @ 100 V, 60 Hz
- Power and Current: 260 W, 2.180 A @ 120 V, 60 Hz
- Power and Current: 257 W, 1.332 A @ 208 V, 60 Hz
- Power and Current: 254 W, 1.179 A @ 230 V, 50 Hz
- Power and Current: 259 W, 1.142 A @ 240 V, 50 Hz

## Certifications / Qualifications

- CE
- IP Rating: IP65, temporary outdoor/wet use

## What's Included

- STRIKE 1
- Seetronic Powerkon IP65 power cord
- Gel frame (8.87 in/225 mm accessories)
- Multi-Bracket