COLORdash Accent Quad



SPECIFICATIONS

Optical

- Light Source: 1 LED (quad-color RGBA) 10 W, (700 mA), 50,000 hours life expectancy

- Beam Angle: 15°
 Field Angle: 29°
 Illuminance (total): 140 lux @ 5 m
 PWM Frequency: 1,200 Hz

Dynamic Effects

- Dimmer: ElectronicShutter/Strobe: Electronic
- Strobe Rate: 0 to 33 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables

FEATURES

- Quad-color LED red, green, blue, amber (RGBA)
 RGBA color mixing via DMX or manually
- Extremely compact with excellent output
- Variable electronic dimmer (0–100%)
 Simple and complex DMX channel profiles for programming versatility

- Double-bracketed yoke doubles as floor stand
 Easy to use OLED digital display
 Built-in auto programs recalled via DMX or Master/Slave

Construction / Physical

- Dimensions: 4.3 x 2.6 x 6.8 in (110 x 67 x 172 mm)
 Weight: 1.8 lb (0.8 kg)
- Exterior Color: Black

Connections

- Power Connection: Edison plug to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
 Cable Length (power): 3.5 ft (1.07 m)

Control

- Control Protocol: DMX
- DMX Channels: 4, 6 or 10
- Modes/Personalities: 3 personalities (4CH, 6CH, 10CH)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
 Power and Current: 14 W, 0.20 A @ 120 V, 60 Hz



Power and Current: 14 W, 0.13 A @ 208 V, 60 Hz
 Power and Current: 13 W, 0.12 A @ 230 V, 50 Hz

Certifications / Qualifications

• CE, MET • IP Rating: IP20, dry location

What's Included

• COLORdash Accent Quad

