

L-SERIES LAMPHEADS

TECHNICAL DATA



L-Series Version	L5-C	L7-C	L10-C	
Type of Lamphead	LED Fresnel	LED Fresnel	LED Fresnel	
Optical System	Focusable Fresnel	Focusable Fresnel	Focusable Fresnel	
Light Aperture	137 mm / 5"	175 mm / 7"	274 mm / 10"	
Beam Angle	14 to 50° Half Peak Angle	15 to 50° Half Peak Angle	15 to 50° Half Peak Angle	
Lamp Type	RGBW LED Light Engine	RGBW LED Light Engine	RGBW LED Light Engine	
White Light	2,800 K to 10,000 K continuously correlated color temperature	2,800 K to 10,000 K continuously correlated color temperature	2,800 K to 10,000 K continuously correlated color temperature	
Colored Light	Full RGB+W color gamut with Hue and Saturation control	Full RGB+W color gamut with Hue and Saturation control	Full RGB+W color gamut with Hue and Saturation control	
Green-Magenta-Adjustment	Continuously adjustable (Full Minusgreen to Full Plusgreen)	Continuously adjustable (Full Minusgreen to Full Plusgreen)	Continuously adjustable (Full Minusgreen to Full Plusgreen)	
Color Rendition	CRI Average > 94 TLCI Average > 90	CRI Average > 94 TLCI Average > 90	CRI Average > 95 TLCI Average > 91	
Color Temperature Tolerance	+/- 100 K (nominal) +/- 1/8 Green-Magenta (nominal)	+/- 100 K (nominal) +/- 1/8 Green-Magenta (nominal)	+/- 100 K (nominal) +/- 1/8 Green-Magenta (nominal)	
Dimming	0 to 100 % continuous	0 to 100 % continuous	0 to 100 % continuous	
Light Output in Battery Mode	100% of total output	n.a.	n.a.	
Mechanical				
Versions	Manual, Pole Operated	Manual, Pole Operated	Manual, Pole Operated	
Handling	Adjustable Sliding Stirrup High-Strength Tilt Lock Pole Operation (Pan, Tilt, Focus)	Adjustable Sliding Stirrup High-Strength Tilt Lock Pole Operation (Pan, Tilt, Focus)	Adjustable Sliding Stirrup High-Strength Tilt Lock Pole Operation (Pan, Tilt, Focus)	
Mounting	16 mm / 28 mm Combo Pin	Spigot 28 mm Junior Pin	Spigot 28 mm Junior Pin	
Housing Colors	blue/silver, black	blue/silver, black	blue/silver, black	
Tilt Angle	+/- 90°	+/- 90°	+/- 90°	
Weight - Manual	5.0 kg / 11.1 lbs	8.2 kg / 18.1 lbs	19.0 kg / 41.1 lbs	
Weight - Pole operated	6.4 kg / 14.2 lbs	10.0 kg / 22.1 lbs	20.5 kg / 44.6 lbs	
Control options				
Control	On-Board Controller, 5-Pin DMX In and Through, Mini-USB			
Remote Device Management (RDM)	DMX Setup, Hour Counter, Standard & Manufacturer, RDM commands			
Software Interface - Mini-USB	DMX Setup, Fixture Status, Firmware Upgrade through PC or Mac			
Wireless Interface	via SkyLink Receiver			
Electrical				
Voltage Input	100 - 240 V~, 50/60 Hz	100 - 240 V~, 50/60 Hz	100 - 240 V~, 50/60 Hz	
Power Consumption	115 W Maximum	220 W Maximum	510 W Maximum	
Lamphead Power Connection	powerCON TRUE1 TOP with Schuko, Edison, Japanese, Chinese, Bare Ends			
Power Switch	On/Off Switch on powerCON TRUE1 TOP cable	On/Off Switch on powerCON TRUE1 TOP cable	On/Off Switch on powerCON TRUE1 TOP cable	
Battery Connector	Male 4-Pin XLR	n.a.	n.a.	
Battery DC Voltage Output	23 to 36 V _{DC}	n.a.	n.a.	
Protection Class / IP Rating	I / IP20	I / IP20	I / IP20	
Ambient Temperature Operation	-20 to +45°C / -4 to +113°F	-20 to +45°C / -4 to +113°F	-20 to +45°C / -4 to +113°F	
Estimated LED Lifetime (L70)	50,000 hours	50,000 hours	50,000 hours	
Estimated Color Shift over Lifetime (CCT)	+/- 5%	+/- 5%	+/- 5%	
Certification	CE, CB, ENEC, cNRTLus, FCC, PSE. Please read the User Manual for more information about the certificates for this product.			
Photometrical Data				
15° - Spot	5 m @ 3,200 K	1,184 lux 110 fc	2,408 lux 224 fc	4,948 lux 460 fc
30° - Middle	5 m @ 3,200 K	356 lux 33 fc	713 lux 66 fc	1,700 lux 158 fc
50° - Flood	5 m @ 3,200 K	136 lux 13 fc	290 lux 27 fc	692 lux 64 fc
15° - Spot	5 m @ 5,600 K	1,336 lux 124 fc	2,704 lux 251 fc	5,552 lux 516 fc
30° - Middle	5 m @ 5,600 K	402 lux 37 fc	796 lux 74 fc	1,900 lux 177 fc
50° - Flood	5 m @ 5,600 K	154 lux 14 fc	323 lux 30 fc	768 lux 71 fc
Accessories				
Accessory Diameter	168 mm / 6.6"	197 mm / 7.8"	344 mm / 13.5" 329 mm / 12.9"	
Accessories for all versions	4-Leaf Barndoor Snoot PowerCON TRUE1 TOP Mains Cable with Line Switch	8-Leaf Barndoor Chimera Lightbank	Filter Frame Speed Ring Circular	
Communication for all versions	SkyLink Stellar			

All specifications are nominal / typical values.



Please visit our website for the latest downloads and to find more information about the ARRI L-Series: www.arri.com

