

# ARTISTE SERIES

## Artiste Rembrandt

With many high-level features already built in, the Artiste series is a family with complete continuity of colours making them an ideal set of tools for operators and designers.

The Artiste Rembrandt is a full-featured LED Wash FX fixture offering outstanding output, optimized wash field and is extremely bright. Providing up to 51,000 lumens, the Rembrandt is the ideal fixture for any application requiring superior wash output, bright and powerful beams and a quiet operation. Integrated with the new SpectraColour system Rembrandt offers a traditional CMY mixing but adds a variable RGB colour mix for rich saturated primaries.

Exclusive to the Artiste Series, the Rembrandt includes a full blackout framing system with 360° continuous index and rotation of shapes.



| FEATURES   |
|--|
| High efficiency 950W 6,500K white LED engine                                   |
| Peak field engine for powerful beams and high center intensity                 |
| Up to 51,000 total lumen fixture output  |
| 6-Position colour wheel, high CRI, UV filter                                   |
| SpectraColor CMYRGB array and variable linear CTO                              |
| Wash beam animation array with 2 independent wheels                            |
| Dual variable frost  |
| Full blackout framing system with 360° continuous index and rotation of shapes |
| 11° to 55° zoom range   Large 180mm fresnel lens                               |
| Optional pebble convex (Stipple PC) lens                                       |
| DMX controllable variable fan modes / Low noise operation                      |

| LIGHT SOURCE  |
|---|
| 950W 6,500K bright white LED engine   |
| 30,000 hour average LED life* *Lamp Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming. |

| COLOURS   |
|---|
| SpectraColor CMY + RGB colour mixing array          |
| 6 Dichroic colours including high CRI filter and UV |
| Linear CTO colour correction                        |

| PHOTOMETRIC DATA  |
|---|
| 51,000 total lumen fixture output                                 |
| CRI 72+ (85 with HCRI filter)                                     |
| Zoom range 11° - 55° (Fresnel) / PC (optional) 8° - 50°           |
| Beam angle 6.1° - 43.1° (Fresnel) / PC (optional) 6.5° - 45°      |
| Field angle 51.9° - 64.9° (Fresnel) / PC (optional) 10.8° - 75.7° |

| EFFECTS  |
|--|
| Motorized zoom                                   |
| 4 Full blackout framing blades                   |
| 360° Framing index - Continuous framing rotation |
| 2 Variable frost filters (medium, heavy)         |
| 2 Bi-directional animation wheels                |
| High speed iris                                  |
| Variable 16-bit dimming curve modes              |
| Focus edge control                               |
| High speed electronic shutter and strobe         |
| Adjustable LED refresh rate frequency            |

### ORDER WITH US TODAY

P: +44 (0) 1279 624 840 E: europe@4wall.com W: www.4wall.com

# ARTISTE SERIES

## Artiste Rembrandt

### GOBOS

- 2 Gobo wheels
- 12 Rotating / Indexing interchangeable glass Gobos

### CONTROL / CONNECTIONS

- 2 DMX channel modes (35 / 59 channels)
- 16-bit pan, tilt and dimming control
- DMX, RDM, Art-NET, sACN protocol support
- 6 Button touch control panel
- Locking 5pin XLR DMX, RJ45 ethernet and power
- Full Color 180° reversible LCD menu display
- Hibernation mode (power save)
- With wired digital communication network

### OPTIONAL ACCESSORIES

- 1237000248- PC Lens

### SIZE / WEIGHT

- Length: 471mm (18.54 in.)
- Width: 333mm (13.11 in.)
- Vertical height (Fresnel lens): 805mm (31.69 in.)
- Vertical height (optional PC lens): 793mm (31.22 in.)
- Weight: 43kg (94.7 lbs.)

### ELECTRICAL / THERMAL

- 1,300W max power consumption
- AC 100-240V - 50/60Hz
- 14°F to 113°F (-10°C to 45°C)
- BTU/hr (+/- 10%) 4433



**ORDER WITH US TODAY**

P: +44 (0) 1279 624 840 E: [europa@4wall.com](mailto:europa@4wall.com) W: [www.4wall.com](http://www.4wall.com)

VIDEO & LIGHTING