# COLORdash Accent Quad



#### SPECIFICATIONS

## Optical

- Light Source: 1 LED (quad-color RGBA) 10 W, (700 mA), 50,000 hours life expectancy

- Beam Angle: 15°
  Field Angle: 29°
  Illuminance (total): 140 lux @ 5 m
  PWM Frequency: 1,200 Hz

# Dynamic Effects

- Dimmer: ElectronicShutter/Strobe: Electronic
- Strobe Rate: 0 to 33 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

#### **Optional Accessories**

- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables

### **FEATURES**

- Quad-color LED red, green, blue, amber (RGBA)
   RGBA color mixing via DMX or manually
- Extremely compact with excellent output
- Variable electronic dimmer (0–100%)
  Simple and complex DMX channel profiles for programming versatility

- Double-bracketed yoke doubles as floor stand
  Easy to use OLED digital display
  Built-in auto programs recalled via DMX or Master/Slave

#### Construction / Physical

- Dimensions: 4.3 x 2.6 x 6.8 in (110 x 67 x 172 mm)
  Weight: 1.8 lb (0.8 kg)
- Exterior Color: Black

# Connections

- Power Connection: Edison plug to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
   Cable Length (power): 3.5 ft (1.07 m)

#### Control

- Control Protocol: DMX
- DMX Channels: 4, 6 or 10
- Modes/Personalities: 3 personalities (4CH, 6CH, 10CH)

#### Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
   Power and Current: 14 W, 0.20 A @ 120 V, 60 Hz



Power and Current: 14 W, 0.13 A @ 208 V, 60 Hz
 Power and Current: 13 W, 0.12 A @ 230 V, 50 Hz

# Certifications / Qualifications

• CE, MET • IP Rating: IP20, dry location

# What's Included

• COLORdash Accent Quad

