

# Unilumin

## Upad IV-S



### GENERAL SPECIFICATION



Pixel Pitch	2.6 mm
LED type	3 in 1 Black SMD
Resolution	192 x 192
Brightness	800 - 1200 cd/m <sup>2</sup>
Refresh Rate	3840 Hz
Module dimensions	500 x 500 x 80 mm
Weight per panel	7.7 kg
IP rating	IP30
Power consumption max./panel	150 W
Power consumption/panel	45 W
Min. viewing distance	2.6 m
Horizontal viewing angle	140°
Vertical viewing angle	120°
Features	-40°~+ 40° curve

### KEY FEATURES

- TRUE CURVE  
Upad IV curved series uses flexible modules and an adjustable frame design to achieve natural and soft curves.
- VARIOUS CREATIVE SHAPES  
Enhanced by nine angle adjustment gears for a single cabinet with  $\pm 40^\circ$  curve range, can be used in conjunction with UpadIV flat and edge panels for more creative applications than ever.
- HDR TECHNOLOGY  
DDC (Dual Drive Configuration) Technology and HDR Technology, using the newest Novastar A10s card, supporting high resolution, 16bit high grey level, 10bit video, automatic module calibration and smart module monitoring.
- IMPRESSIVE VIEWING EXPERIENCE  
With  $\geq 95\%$  DCI-P3 colour gamut content restoration.

### ORDER WITH US TODAY

P: +44 (0) 1279 624 840 E: europe@4wall.com W: www.4wall.com

