

### GENERAL SPECIFICATION



Pixel Pitch	2.6 mm
LED type	3 in 1 Black SMD
Resolution	192 x 192
Brightness	1000 cd/m <sup>2</sup>
Refresh Rate	3840 Hz
Module dimensions	500 x 500 x 70 mm
Weight per panel	6.3 kg
IP rating	IP30
Power consumption max./panel	120 W
Power consumption/panel	40 W
Min. viewing distance	2.6 m
Horizontal viewing angle	140°
Vertical viewing angle	120°
Features	-5° - 10° curve

### KEY FEATURES

- **ULTRA LIGHTWEIGHT**  
Die-cast magnesium design, weighs only 6.3kg.
- **PRECISE CURVED FAST LOCK**  
From -5 °(convex) to +10° (concave), wide range of curving, creative screen shapes and sizes.
- **HDR TECHNOLOGY**  
DDC (Dual Drive Configuration) Technology and HDR Technology, using the newest Novastar A10s card, supporting high resolution, 16bit high grey level, 10bit video, automatic module calibration and smart module monitoring.
- **MULTIPLE SCENARIO APPLICATIONS**  
High precision curving and creative display, all Upad IV panels come from the same batch and can be used in conjunction with our 90-degree edge and Upad-S True Curve creative panels
- **AUTOMATIC LOCK DESIGN**  
Enables one engineer to finish installation, disassembly and maintenance.

### ORDER WITH US TODAY

P: +44 (0) 1279 624 840 E: [europe@4wall.com](mailto:europe@4wall.com) W: [www.4wall.com](http://www.4wall.com)