

Vanish ST

Title	V4ST	V6ST
Pixel Pitch	4.6mm	6.94mm
LED Configuration	SMD 1921 Black	SMD 1921 LED
Max Brightness Calibrated	5000nits	5000nits
Panel Dimension	1000mm x 1000mm x 116mm 39.4" x 39.4" x 4.57"	1000mm x 1000mm x 116mm 39.4" x 39.4" x 4.57"
Panel Resolution (H x V)	216 x 216	144 x 144
Weight Per Panel	27.5kg 60.63lbs	27.3kg 60.19lbs
Power Consumption Max/Average	700W / 350W	700W / 350W
BTU Max/Average	2390 / 1100	2390 / 1100
Transparency	Solid	Solid
Serviceability	Rear	Rear
Curving (Concave & Convex)	Concave 10° - Convex 10°	Concave 10° - Convex 10°
Viewing Angle Vertical	120°	120°
Viewing Angle Horizontal	160°	160°
Refresh Rate	3840Hz	3840Hz
Gray Scale	16bit	16bit
Operational Temp/Humidity	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR
Storage Temp/Humidity	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR
IP Rating	Outdoor	Outdoor

Certifications	CE, ETL, FCC, UKCA	CE, ETL, FCC, UKCA
Scan Ratio	1/6	1/4
Max. Hanging	12 panels	12 panels
Max. Stacking	6 panels	6 panels

Please note: The specifications are for reference only, actual values may vary. For the complete disclaimer, please go to <https://www.roevisual.com/disclaimer>.