

 **VORTEX** 



Redefining Nothing.
It's all you.

650W
Power

IP65
Water Resistant

14000lux
@3m/9.8ft

PSU
Inside

VORTEX8 OVERVIEW



The Vortex8 is a versatile 2x1 RGBW system with a CCT range from 2200K to 15000K that can be used as a hard punch light to bounce or push through diffusion, or as a creamy soft light with the Creamsource Dome or DoPchoice Snapbag. Effects and colour gels are built into the latest CreamOS architecture in addition to a range of new features wrapped into an intuitive user interface. Unpredictable weather and messy effects machines are no longer a worry for the lighting department where the Vortex is in place. The Vortex8 is IP65 water resistant and sealed for the ultimate security and efficiency. Rain, snow and dust wont hold the Vortex8 back.

Connectivity to the Vortex8 is well up to date with LumenRadio TimoTwo built in, Ethernet, Bluetooth, 5pin DMX, Wifi, USB type A and Creamsource Accessory port. Interaction between Vortex8 and various third party instruments and protocols are endless opening various wired and wireless control options. We are geeks for high quality and precision engineering, and loads of our geekiness has spilled into the Vortex Series. Built with elegance and durability in mind the aluminium machining and technopolymer infusion has allowed us to achieve our goals. Containment and simplicity is also achieved in this design, with the PSU as well as the antennas integrated into the head.

We stand by our users offering 5 years Warranty when you register your product. Go to www.creamsource.com for more information.



PHOTOMETRIC NAKED 20°



OVERVIEW

3200K
 CRI 97.0
 CRI (Re) 96.2
 TLCI 94.0
 CQS 95.7
 Rf 94.9
 Rg 103.3

5600K
 CRI 95.3
 CRI (Re) 93.9
 TLCI 96.4
 CQS 96.3
 Rf 93.1
 Rg 103.4

www.creamsource.com

VORTEX8 SPECS

| | |
|--------------------------------|---|
| Material | Aluminium/Technopolymer |
| Light Source | RGBW LED |
| Colour Range | CCT: 2200 - 15000K, PLUS/MINUS GREEN, HUE/SATURATION, XY, GELS, DIRECT RGBW, EFFECTS |
| CRI | Typical 95 |
| TLCI | Typical 95 |
| Beam Angle, SPOT Lens | 20° (Half Peak Angle) |
| Tilt Angle | 360° |
| Photometrics | <p>3200K:</p> <p>68,200 lx / 6,340 fc @ 1m / 3.3ft 26,200 lx / 2,430 fc @ 2m / 6.6ft 12,700 lx / 1,180 fc @ 3m / 9.8ft 7,400 lx / 690 fc @ 4m / 13.1ft 4,800 lx / 450 fc @ 5m / 19.4 ft 3,400 lx / 320 fc @ 6m / 19.7 ft</p> <p>5600K:</p> <p>73,500 lx / 6,830 fc @ 1m / 3.3ft 28,600 lx / 2,660 fc @ 2m / 6.6ft 13,900 lx / 1,290 fc @ 3m / 9.8ft 8,000 lx / 740 fc @ 4m / 13.1ft 5,200 lx / 480 fc @ 5m / 19.4 ft 3,700 lx / 340 fc @ 6m / 19.7 ft</p> |
| Mounting | 8x 3/8" Threaded Insert Rigging Points |
| Yoke | Removable quick release yoke |
| Filter Rails | 2 Filter Rails for Secondary Lenses, Diffusers, Accessories |
| User interface | High Precision Digital Magnetic Encoder, Backlit Keypad, Colour LCD Display |
| Dimming | 0-100% with High Resolution, Super-Smooth Low End Mode |
| High Speed Capability | Over 5000fps Flicker Free in High Speed Mode |
| Synchronization | Sync Input for Triggering and Syncing to Camera Shutter |
| Max Ambient Temperature | 40°C |
| Cooling | Low noise variable speed fans |
| Estimated LED Lifespan | 50,000hrs (L70) |
| Input (AC) | 100-240V AC, 50/60Hz, Max 6.6A, 660W. Neutrik PowerConTrue connector |
| Input (DC) | 48V DC, Max 13.75A, Can run at 100% brightness on DC input |
| Protection Class | IP65 |
| Weight | 15.9kg / 35lb (Excluding Yoke) 1.93kg / 4.2lb (Yoke weight) |
| Dimensions | 690 x 380 x 121mm / 27.2" x 15" x 4.8" (Excluding Yoke) 831 x 551 x 164mm / 32.7" x 21.7" x 6.4" (Including Yoke) |
| Warranty | 3 Years on Fixtures, 12 Months on Accessories (5 Years registered) |
| Certifications | Pending: CE, ETL and FCC |
| Control | On-Board Interface, DMX via standard 5-pin XLR connectors, Wired Remote Control Accessory, Integrated Lumen radio Timo Two with Bluetooth, Ethernet, USB Type A |
| Includes | Vortex8 650W Colour, Yoke, Power cable, Flat diffuser |
| Product Code | K-CSV-8-ESS |