

# WELL FIT X

## FEATURES

- A fully realized kit of (6) battery operated chrome IP65-rated uplight-style fixtures with (9) RGB warm white LEDs, and a beam angle of 11.3 degrees
- Charging case designed to charge with the lid closed to save warehouse space
- Battery run time selections of 5, 8, 12, and 18 hours of operation at full output
- Built-in battery charger allows fixture to operate while charging
- Control over RDM, CRMX, or RF
- Easy connection to WELL CONNECT box and ConnectFX app
- USB-C port for convenient software updates
- Pressure equalizing M6 Gore valve
- Adjustable front foot for adjusting fixture angle
- Kensington lock position
- Built-in safety cable attachment point
- Easy-to-read OLED display
- Built-in theft alarm (audio and visual notification)
- Built-in PWM adjustment
- Included RF remote
- Included 6 pack charging case



---

## SPECIFICATIONS

### OPTICAL

- Light Source: 9 LEDs (RGBWW) 13.2 W, (556 mA), 50,000 hours life expectancy
- Color Temperature (range): 2600 to 10,000K
- Beam Angle: 11.5°
- Field Angle: 21.1°
- Lumens: 1762 lm (OFF battery setting)
- Illuminance: 1087 lux @ 5 m (OFF battery setting)
- Lumens: 1944 lm (5-hour battery setting)
- Illuminance: 1205 lux @ 5 m (5-hour battery setting)
- Lumens: 1233 lm (8-hour battery setting)
- Illuminance: 764 lux @ 5 m (8-hour battery setting)
- Lumens: 821 lm (12-hour battery setting)
- Illuminance: 507 lux @ 5 m (12-hour battery setting)
- Lumens: 550 lm (18-hour battery setting)
- Illuminance: 339 lux @ 5 m (18-hour battery setting)
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000 Hz

### DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic

- Strobe Rate: 0 to 30 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: No

## CONSTRUCTION / PHYSICAL

- Dimensions - Fixture: 4.9 x 4.9 x 6.9 in (126 x 126 x 176 mm)
- Dimensions - 6 pack case: 21.8 x 18.5 x 13.5 in (554 x 470 x 345 mm)
- Weight (single unit) 7.0 LB (3.2 kg)
- Exterior Color: Chrome
- Housing Material: Aluminum diecast

## CONNECTIONS

- Power Connection: 5.5mm right-angle barrel jack
- Cable Length (charger): 8.5 ft (2.6m) (sold separately)
- Power Input (charging case): Seetronic TRUE1 IP65
- Power Output (charging case): Seetronic TRUE1 IP65
- Software Connection: USB-C

## CONTROL

- Control Protocol: RDM, CRMX, NFC, RF
- DMX Channels: 5, 8, or 12
- Modes/Personalities: 3 personalities (5Ch, 8Ch, 12Ch)
- Wireless WDMX "G" Compatibility: G4S
- Wireless Lumen Radio Compatibility: CRMX

## ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Single unit <ul> <li> Power and Current (single unit charging): 43 W, 0.74 A @ 100 V, 60 Hz <li> Power and Current (single unit charging): 42 W, 0.64 A @ 120 V, 60 Hz <li> Power and Current (single unit charging): 42 W, 0.52 A @ 208 V, 60 Hz <li> Power and Current (single unit charging): 42 W, 0.47 A @ 230 V, 50 Hz <li> Power and Current (single unit charging): 42 W, 0.47 A @ 240 V, 50 Hz </ul>
- 6 Pack case <ul> <li> 3 units @ 120 V; 4 units @ 208 V; 5 units @ 230 V <li> Power and Current: 239W, 3.94A @ 100V <li> Power and Current: 238W, 3.44A @ 120V <li> Power and Current: 235W, 2.48A @ 208V <li> Power and Current: 235W, 2.32A @ 230V <li> Power and Current: 235W, 2.27A @ 240V </ul>

## BATTERY

- Battery type: Lithium Ion
- Rechargeable: Yes
- Battery Charge Time: 1.6 hours
- Battery Life: 3hr, 5hr, 8hr, 12hr
- Battery Power: 25.9 V, 4.4 Ah

## CERTIFICATIONS / QUALIFICATIONS

- CE, FCC, UKCA
- IP Rating: IP65, temporary outdoor/ wet use (fixture)
- IP Rating: IP20 (case)
- Temperature (startup): -4 °F to 113 °F (-20 °C to 45 °C)

- Temperature (operating): -22 °F to 113 °F (-30 °C to 45 °C)

## WHAT'S INCLUDED

- (6) WELL FIT X
- (1) 6 slot charging case
- (1) basic RF controller
- (1) True 1 power cable
- (1) QRG

## OPTIONAL ACCESSORIES

- Clamps
- WELL FIT X - 15° Filter Pack
- WELL FIT X - 60° x 10° Filter Pack
- WELL FIT X - Single Charger
- WELL FIT X - Black Fixture Cover
- [W-DMX Micro T-1 TRX G6](https://www.chauvetprofessional.com/products/w-dmx-micro-t-1-trx-g6/)