Rogue Outcast 1L Beam

FEATURES

- Fully featured, high powered IP65 rated LED beam fixture
- Lightweight and durable aluminum/magnesium alloy body
- Fast and precise movement of pan and tilt functions
- Individually controllable and layerable 5- and 8-facet prisms
- Frost for softening beam edges and effects
- 5-pin DMX input/output connections
- Tight 1.4° beam for extremely focused areal effects
- RDM enabled for remote addressing and troubleshooting
- 7 rotating and 7 static gobos on one wheel for dynamic gobo effects
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility
- USB-C port for uploading software

SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (CW) 140 W, (4 A), 50,000 hours life expectancy
- Color Temperature (at full): 6928 K
- Front lens diameter: 160 mm
- CRI: 69.3
- Beam Angle: 1.4°
- Field Angle: 1.7°
- Cutoff Angle: 1.8°
- Lumens – Source: 5500
- Lumens – Output: 3218
- Illuminance (total) : 224,670 lux @ 5 m

DYNAMIC EFFECTS

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 14 + white, split colors, continuous scroll at variable speeds
- Gobos: 14 + open (14 metal), 7 rotating, 7 static, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobo Size: Gobo Wheel (rotating): Positions 2, 4, 6, 8, 10, 12 and 14 (metal); size: 9.8 mm (outside), 5 mm (image), 0.6 mm (max. thickness)
- Dimmer: Electronic
- Shutter/Strobe: Motorized
- Focus: Motorized
- Frost: Motorized

- Prism: 5 Facets, motorized, linear, rotating
- Prism: 8 Facets, motorized, round, rotating
- Move-in-Black: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 12.56 x 8.58 x 19.88 in (319 x 218 x 505 mm)
- Weight: 35.4 lb (16.1 kg)
- Exterior Color: Black
- Housing Material: Aluminum/Magnesium diecast

CONNECTIONS

- Power Connection: Bare ended to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 17 or 19
- Modes/Personalities: 2 personalities (17, 19)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 233 W, 2.08 A @ 120 V, 60 Hz
- Power and Current: 226 W, 1.15 A @ 208 V, 60 Hz
- Power and Current: 223 W, 1.04 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, UKCA,
- IP Rating: IP65, temporary outdoor/ wet, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -14 °F to 113 °F (-10 °C to 45 °C)
- Maximum Exterior Surface Temperature (Tc): 80° C / 176° F
- Maximum Ambient Temperature (ta): 45° C / 113° F
- Noise Level (Idle) : 24.7 dB(A) @ 1 m
- Noise Level (Max): 35.3 dB(A) @ 1 m
- Noise Level (Auto) : 36.4 dB(A) @ 1 m
- Noise Level (ECO) : 36.5 dB(A) @ 1 m
- Noise Level (Full): 43.3 dB(A) @ 1 m

WHAT'S INCLUDED

- Rogue Outcast 1L Beam
- Seetronic Powerkon IP65 power cord
- (2) Omega brackets with mounting hardware

OPTIONAL ACCESSORIES

- Clamps
- IP65 5 pin DMX Cables
- IP65 PowerKon Extension cables
- Flight Case